

WINIpump WPF20, To pump with wine's respect

Long distance remote control &
serial speed variation



Polyvalente



- ✓ **Strong aspiration**
(> -5 m)
- ✓ **Ergonomic**
(Driving stand and adapted remote control)
- ✓ **Cumbersomeless**
(adjustable fitting)
- ✓ **Full stainless steel**
- ✓ **Flexible impeller pump**
with slow rotation speed
- ✓ **Suits to clear wine but**
also musts, and lees

❑ **Wide operating range :**

- From 10 to 200 hl/h

❑ **Optional :**

- Intone système
(Automatic stop on closed valve
at aspiration and suppression)
- WINIcompteur
(electromagnetic counter
which allows a trustly
measure of flow and volumes)





Pump specifications

Parts in contact with the wine	AISI 316L
Trolley and rest of the pieces	AISI 304
Impeller	Neoprene
Connections	Mâcon 50
Maximum flow	200 hl/h
Maximum pressure	4 bar
Maximum temperature	80°C

Electrical specifications

Power supply	400 V/AC 50/60hz
Engine power	2,2 kw
Maximum electric power	10 A
Connections	Prise Hypra 3P+T 16A (others on request)
Cable's length	10 m
Electric panel	IP64

20160505 FTWPF20 ENG

24 months warranty



2 rue du petit cotat
89800 MALIGNY
Tél : 03 86 33 46 53



@mail : contact@planeteconcept.com